

78100

781.00

Designer Note: Intended for usage with Flexible Delineators (635.00). Discuss usage with the Traffic Operations Engineer and Traffic Control Specialist.

TEMPORARY RAISED REFLECTIVE PAVEMENT MARKER

Effective October 1, 1995 Revised January 1, 2007

Markers shall meet the requirements of Section 781 of the Standard Specifications as modified herein:

Each marker shall be bi-directional, approximately 2-1/2" (65 mm) high with a base size of approximately 6" (150 mm) by 13" (330 mm), as manufactured by Astro Optics Corporation or an approved equal.

The markers shall have a minimum of 4 square inches (2580 mm²) of reflective area on each face. The reflectors shall meet the minimum reflectivity requirements of Article 1096.02.

The markers shall be placed 25' (7.5 m) on each side of each flexible delineator post.

These markers shall be maintained throughout the project. When the project is completed, the marker shall be removed in a manner which will cause the least damage to the pavement surface. Should any damage result from the removal of the markers, the Contractor shall repair the damaged surface to the satisfaction of the Engineer.

Basis of Payment. This work will be paid for at the contract unit price each for TEMPORARY RAISED REFLECTIVE PAVEMENT MARKER, which price shall include furnishing, installing, maintaining, and removing the marker, and the cost of repairing damaged surface resulting from the removal.