

SUGGESTED ITEMS FOR INCLUSION IN THE SURVEY REPORT

A. INTRODUCTION

Describe the buildings being surveyed for asbestos abatement. Review the data provided by IDOT to the consultant and data available from other sources.

B. SAMPLING

Describe the material of the sample such as floor tile and mastic. Describe the location of each sample such as east bedroom floor. Samples of non-suspect materials, which include the following, should not be taken:

1. Concrete, mortar, concrete masonry units, brick, ceramic glazed block or brick, ceramic tile, structural clay tile and terrazzo
2. Metals, glass and vitreous china (plumbing fixtures)
3. Wood, plywood, veneered paneling, plastic laminates
4. Fabrics other than fire curtains and fire blankets
5. Caulk
6. Fiberglass, foam glass, rubber insulation

C. MATERIALS TABLES

1. The following minimum data regarding each sample should be submitted:
 - a. Material description such as floor tile and mastic
 - b. Type and percentage of asbestos such as chrysotile, 4%
 - c. Location and description of asbestos containing material and sample number (for example, east bedroom, 6" x 12" cork tile and mastic, sample number 8)
 - d. Quantity of asbestos containing material such as 700 square feet
 - e. Percent friable
2. The data for each sample should be in the format as shown below:

Building No.	Parcel No.	Sample No.	Location	Materials	Asbestos Yes/No	Quantity of ACM	Asbestos Type	Percent of Asbestos	Percent Friable
--------------	------------	------------	----------	-----------	-----------------	-----------------	---------------	---------------------	-----------------

D. DRAWINGS

Submit drawings of buildings indicating locations of samples as well as locations of asbestos containing materials.

E. COST ESTIMATE OF ASBESTOS

Submit data and calculations justifying the basis of arriving at the cost estimate of asbestos.